

EXANE[®]-Transit

Multi-Conductor Cable



110 °C • Multi-Conductor Cable • 600V
AAR S-501/RP-585 • XLPO Insulation and Jacket

FEATURES

- **Wide temperature range -55 °C to 110 °C**
- **Thermoset Insulation and jacket**
- **Superior mechanical properties**
- **Flexible construction**
- **Flame retardant**
- **Excellent fluid/oil resistance**
- **Moisture and sunlight resistant**
- **Employs Exane 1068A insulated conductors**

PERFORMANCE STANDARDS

- **AAR S-501**
- **AAR RP-585**
- **ICEA S-66-524 (5-95-658)**
- **Passes the spread of fire and smoke emission in accordance with NFPA 130-2010 article 8.6.7.1.1 FT4/IEEE 1202 with smoke per UL1685**
- **Passes UL VW-1 flame test**
- **Passes IEEE-383 1974 vertical tray flame test**
- **Meets requirements of 49 CFR Part 238 for flame and smoke requirements**
- **Meets transit toxicity requirements when tested in accordance with BSS 7239**
- **Meets transit smoke requirements when tested in accordance with ASTM E662**

CONSTRUCTION

Conductor: Annealed, Tinned copper per ASTM B33, B172, AAR S-501, and AAR RP-585

Insulation: Crosslinked polyolefin, Exane[®] (colors-as required)

Colors: As required

Binder: Polyester tape

Shields: Tin copper braid (optional)

Jacket: Cross-linked polyolefin Exane[®] Jacket

*** RSCC rated 110 °C**

SCOPE

Exane[®] multiconductor transit cables are a rugged, flame retardant construction. They are suitable for installation indoors or outdoors in metals trays, conduit, underground duct, or for direct burial. The cables have excellent flexibility and resist crush, low temperature cracking, moisture and petrochemical fluids. The Exane[®] thermoset insulation system provides a conductor component with superior cut-through, abrasion resistance and electrical overload characteristics.

CHICAGO

933 E. Remington Rd
Schaumburg, IL 60173
847.944.1500

BOSTON

100 Jytek Drive
Leominster, MA 01453
978.534.5300

ATLANTA

5940 Cabot Parkway
Alpharetta, GA 30005
678.297.1080

PHOENIX

1524 W 14th Street
Tempe, AZ 85281
623.478.8700

EXANE[®]-Transit

Multi-Conductor Cable, 110 °C, 600V



Product Code	Number of Conductors	Conductor Size (AWG)	Stranding	Insulated Conductor OD IN	Jacket Thickness IN	Cable OD IN	Weight LBS per 1000 FT	Technical Drawing
--------------	----------------------	----------------------	-----------	---------------------------	---------------------	-------------	------------------------	-------------------

Exane[®]: Two Conductor Shielded (TC Braid) With Exane Jacket

TXE 2/C 18S(Exane)	2	18	19/30	0.109	0.045	0.339	67	TD-002603
TXE 2/C 16S(Exane)	2	16	19/29	0.116	0.045	0.353	74	TD-002604
TXE 2/C 14S (Exane)	2	14	19/27	0.129	0.045	0.370	88	TD-008751
TXE 2/C 12S (Exane)	2	12	19/25	0.147	0.045	0.410	116	TD-003086

Exane[®]: Three Conductor Shielded (TC Braid) With Exane Jacket

TXE 3/C 18S (Exane)	3	18	19/30	0.109	0.045	0.346	81	TD-002605
TXE 3/C 16S (Exane)	3	16	19/29	0.116	0.045	0.371	92	TD-002606
TXE 3/C 14S (Exane)	3	14	19/27	0.129	0.045	0.400	120	-
TXE 3/C 12S (Exane)	3	12	19/25	0.147	0.045	0.438	145	-

Exane[®]: Four Conductor Shielded (TC Braid) With Exane Jacket

TXE 4/C 18S (Exane)	4	18	19/30	0.109	0.045	0.374	92	TD-003085
TXE 4/C 16S (Exane)	4	16	19/29	0.116	0.045	0.402	109	TD-002607
TXE 4/C 14S (Exane)	4	14	19/27	0.129	0.045	0.427	130	TD-008673
TXE 4/C 12S (Exane)	4	12	19/25	0.147	0.045	0.480	187	TD-003801

Exane[®]: Two Conductor Non-Shielded With Exane Jacket

TXE 2/C 18 (Exane)	2	18	19/30	0.109	0.045	0.315	50	TD-006377
TXE 2/C 16(Exane)	2	16	19/29	0.116	0.045	0.331	59	TD-005309
TXE 2/C 14(Exane)	2	14	19/27	0.129	0.045	0.351	68	-
TXE 2/C 12(Exane)	2	12	19/25	0.147	0.045	0.395	100	-

Exane[®]: Three Conductor Non-Shielded With Exane Jacket

TXE 3/C 18(Exane)	3	18	19/30	0.109	0.045	0.330	70	TD-006512
TXE 3/C 16(Exane)	3	16	19/29	0.116	0.045	0.340	73	TD-004426
TXE 3/C 14(Exane)	3	14	19/27	0.129	0.045	0.371	86	-
TXE 3/C 12(Exane)	3	12	19/25	0.147	0.045	0.410	115	-

Exane[®]: Four Conductor Non-Shielded With Exane Jacket

TXE 4/C 18(Exane)	4	18	19/30	0.109	0.045	0.362	74	-
TXE 4/C 16(Exane)	4	16	19/29	0.116	0.045	0.375	90	TD-005279
TXE 4/C 14(Exane)	4	14	19/27	0.129	0.045	0.427	130	-
TXE 4/C 12(Exane)	4	12	19/25	0.147	0.045	0.453	145	-

Exane[®] is a registered trademark RSCC Wire & Cable LLC

CHICAGO
933 E. Remington Rd
Schaumburg, IL 60173
847.944.1500

BOSTON
100 Jytek Drive
Leominster, MA 01453
978.534.5300

ATLANTA
5940 Cabot Parkway
Alpharetta, GA 30005
678.297.1080

PHOENIX
1524 W 14th Street
Tempe, AZ 85281
623.478.8700

For sales inquiries: sales@electrowire.com